# ProLite B1702S-W2 | 17 inch

The new 'B' series of displays from iiyama means what it stands for; Business. The impressive specification and feature set offers superb picture quality and flexibility for Business applications with integrated Height Adjustability in the stand. The core component is a high-grade TN panel with a 1.3 megapixel resolution, high contrast ratio and powerful brightness ensuring optimum picture quality. Comprising of both Analogue and Digital inputs with free Digital cable compatibility with your system is assured. The PLB1702S is available in Black or Ivory.

| | | |
|---|---|---|
| LCD Panel | **Panel** | TN |
| | **Diagonal** | 17" (43 cm) |
| | **Display area h x w** | 270.3 x 337.9 mm |
| | **Response time** | 5 msec |
| | **Contrast ratio** | 1000 : 1 typical |
| | **Brightness** | 300 cd / m² typical |
| | **Viewing zone** | horizontal/vertical: 160°/160°;<br>right/left: 80°/80°;<br>up/down: 80°/80° |
| | **Display colour** | 16.7 Million |
| | **Pixel pitch h x v** | 0.294 x 0.294 mm |
| | **Native resolution** | 1280 x 1024 (1.3 MegaPixel) |
| Electronics | **Horizontal sync** | 24 - 80 KHz |
| | **Vertical sync** | 55 - 75 Hz |
| | **Bandwidth** | 135 MHz |
| | **Input connector** | D-Sub, DVI-D |
| | **Speaker** | 2 x 1W |
| | **Included accessories** | power cable, D-Sub cable, DVI-D signal cable, audio cable, user manual, cable holder |
| | **Apple - Mac** | All iiyama monitors are compatible with Apple-Macintosh computers |
| | **Controls** | On-Screen-Display in 6 languages (D, GB, ESP, F, I, JP) and 5 Front controls(Menu, + Button (Volume+), Power, - Button (Volume -), Auto) |
| | **User controls** | brightness, contrast, clock, phase, V-position, H-position, colour temperature, auto set-up, sharpness, gamma, economy mode, OSD language, OSD position, OSD time out, signal select, volume |
| | **Driver** | Windows 95 / 98 / 2000 / ME / XP |
| | **Ergonomics** | TCO '03, TÜV-Ergonomics |
| | **Safety** | TÜV GS, FCC-B, UL / C-UL, CE, VCCI-B, GOST-R, CCC |
| | **Power supply** | AC 100 - 240 V, 50 / 60 Hz |
| | **power supply unit** | internal |
| | **Power usage** | max. 40 W in normal use, max. 2 W in Power management mode |
| | **Power management** | VESA DPMS, ENERGY STAR® |
| Mechanical | **Anti-theft-device** | Kensington-lock prepared |
| | **VESA mounting** | 100 mm |
| | **Height adjustment** | 110 mm |
| | **Swivel Stand** | 70°, each 35° right and left |
| | **Tilt angle** | 25° up, 5° down |
| | **Weight** | 5.5 kg |
| | **Dimensions w x h x d** | 370.5 x 397 - 507 x 236.5 mm |

**All trademarks and registered trademarks acknowledged. E & O E. Specifications subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defaults.**

Megapixel describes the size of your desktop and therefore the amount of information your display can show. A lcd with a physical resolution of 9.2 mega pixels (3840 x 2400) can show 6 times more information than a display with 1.3 mega pixels (1280 x 1024). That means your desktop is about 600 percent bigger.